



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CMB-S-35	37.4	15&18&22	200
CMB-S-34	34	16&19&22	200
CMB-S-32	32	15&18&22	200
CMB-S-7437	34.5	15&18	200
CMB-S-9040	34.5	15&18&22	200
CMB-16-19	16	8,12,15,18	200

Mechanical Bottomer CMB-S

The Mechanical Bottomer satisfy the simplest exigencies in cardboard bottom sealing. Its use is particularly advisable when packages are to be filled in different locations and in limited quantities.

Length:910mm
Width:600mm
Height:1245mm
Weight:26.8kg



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CAB-S-35	34.7	15&18&22	200
CAB-S-34	34	16&19&22	200
CAB-S-32	32	15&18&22	200
CAB-S-7437	34.5	15&18	200
CAB-S-9040	34.5	15&18&22	200
CAB-16-19	16	8,12,15,18	200

Pneumatic Bottomer CAB-S

When the production output requires sealing of 50 to 100 carton bottoms per hour, the use of a Pneumatic Bottomer is advisable. This model is equipped with a safety foot pedal.

Length:830mm
Width:600mm
Height:1245mm
Weight:22.7kg
Air Pressure:5.5-6kg/cm2



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CMS-S-35	34.7	15&18&22	200
CMS-S-34	34	16&19&22	200
CMS-S-32	32	15&18&22	200
CMS-S-7437	34.5	15&18	200
CMS-S-9040	34.5	15&18&22	200
CMS-16-19	16	8,12,15,18	200

Mechanical Side Bottomer CMS-S

The Mechanical Side Bottomer satisfy the simplest exigencies in stapling lids and sides for cartons. Its use is particularly advisable when packages are to be filled in different locations and in limited quantities.

Length:910mm
Width:600mm
Height:1245mm
Weight:25.8kg



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CAS-S-35	34.7	15&18&22	200
CAS-S-34	34	16&19&22	200
CAS-S-32	32	15&18&22	200
CAS-S-7437	34.4	15&18	200
CAS-S-9040	34.4	15&18&22	200
CAS-16-19	16	8,12,15,18	200

Pneumatic Side Bottomer CAS-S

When the production output requires sealing of 50 to 100 lids and sides for carton per hour, the use of a Pneumatic Side Bottomer is advisable. This model is equipped with a safety foot pedal.

Length:830mm
Width:600mm
Height:1245mm
Weight:22.7kg
Air Pressure:5.5-6kg/cm2
Working Height:930mm



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CAS-S-35-125	34.7	15&18&22	200
CAS-S-34-125	34	16&19&22	200
CAS-S-32-125	32	15&18&22	200
CAS-S-7437-125	34.4	15&18	200
CAS-S-9040-125	34.4	15&18&22	200

Pneumatic Side Bottomer CAS-S-125

When the production output requires sealing of 50 to 100 lids and sides for carton per hour, the use of a Pneumatic Side Bottomer is advisable. The working height could be 1250mm for bigger carton. This model is equipped with a safety foot pedal.

Length:830mm
Width:600mm
Height:1550mm
Weight:26.5kg
Air Pressure:5.5-6kg/cm2
Working Height:1250mm



MODEL NO.	STAPLE'S DIMENSION		CAPACITY
	CROWN (mm)	LENGTH (mm)	
CAS-S-35-155	34.7	15&18&22	200
CAS-S-34-155	34	16&19&22	200
CAS-S-32-155	32	15&18&22	200
CAS-S-7437-155	34.4	15&18	200
CAS-S-9040-155	34.4	15&18&22	200

Pneumatic Side Bottomer CAS-S-155

When the production output requires sealing of 50 to 100 lids and sides for carton per hour, the use of a Pneumatic Side Bottomer is advisable. The working height could be 1520mm for bigger carton. This model is equipped with a safety foot pedal.

Length:830mm
Width:600mm
Height:1850mm
Weight:28.5kg
Air Pressure:5.5-6kg/cm2
Working Height:1520mm